DEWALT

20V MAX* BRUSHLESS XR®

# BEST CONTROL WITH FASTEST MATERIAL REMOVAL VS. LEADING COMPETITORS**

## DCW211B
## 20V MAX* XR® 5 IN. RANDOM ORBITAL SANDER (TOOL ONLY)

Designed to maximize productivity for the professional woodworker, remodeler, carpenter and general contractor, the 20V MAX* XR® 5 in. Random Orbital Sander offers the best control with fastest material removal vs. leading competitors** (battery and charger sold separately). Ideal for small surfaces and tight spaces, this sander sands up to 50 sq-ft. and leaves a fine finish††. As our best performing 20V MAX* 5 in. random orbital sander, the 20V MAX* XR® 5 in. Random Orbital Sander delivers fast material removal, adjustable speed, and outstanding control‡‡.

CARPENTRY TOTAL SOLUTIONS™




Battery sold separately

*Maximum initial battery voltage (measured without a workload) is 20 volts. Nominal voltage is 18.
**vs. leading competitors' cordless 5" random orbit sanders; vibration based on steel plate, 50N bias force, 180 grit; material removal based on pine, 3kg bias force, 80 grit.
††Per charge, on high speed, removing 3.8g, 80 grit, 3kg bias force on pine, using DCB205 (sold separately).
‡‡Material removal rate and vibration using DCB205 (sold separately).

DCW211BSS

# 20V MAX* XR® 5 IN. RANDOM ORBITAL SANDER (TOOL ONLY)

**EQUIPPED WITH DEWALT® AIRLOCK™ SYSTEM**
Collects up to 95% of dust*** (dust extractors sold separately)

**HELP MINIMIZE CLEAN-UP**
WIRELESS TOOL CONTROL enables vacuum operation (vacuum sold separately)

**PERFORM PROTECT ANTI-VIBRATION**



**CHIP-READY** TRACK THIS TOOL
DEWALT® Chip Sold Separately.

**WORK IN CONFINED AREAS**
Our lowest profile 5 in. random orbital sander‡

**VARIABLE SPEED CONTROL**
5 speeds from 8,000 - 12,000 (no load) OPM

**HOOK AND LOOP 8-HOLE PLATEN/PAD**

*Maximum initial battery voltage (measured without a workload) is 20 volts. Nominal voltage is 18.
***On high speed, 80 grit, 3kg bias force on oak, using DWV015 (sold separately).
†On high speed, 180 grit, 50N bias force on steel plate using DCB205 battery (sold separately) vs. DCW210.
‡Height, tool only
DEWALT PERFORM & PROTECT™ line of tools is designed to provide a high level of one or more of the following: dust containment, control, or low vibration, without sacrificing performance.




MINIMIZE FATIGUE: Up to 40% less vibration†




WORK IN CONFINED AREAS: Our lowest profile 5 in. random orbital sander‡

## SPECIFICATION

| | |
|---|---|
| ORBITS PER MINUTE | 8,000-12,000 (no load) OPM |
| ORBIT DIAMETER | 7/64 in. |
| HEIGHT | 4.37 in. |
| PAD TYPE | Hook and Loop |

## WARRANTY

| TOOL WARRANTY | | |
|---|---|---|
| 3 YEAR | 1 YEAR | 90 DAY |
| LIMITED WARRANTY | FREE SERVICE | MONEY BACK GUARANTEE |

## PRODUCT OFFERINGS

### DCW211B

(1) DCW211 20V MAX* XR® 5 in. Random Orbital Sander (Tool Only)

(1) 8 Hole 80 Grit Sandpaper

(1) DCE042 TOOL CONNECT™ Chip Adapter (chip sold separately)



## RELATED PRODUCTS

### DCW230B

20V MAX* XR® 6 in. Random Orbital Sander (Tool Only)



### DCW200B

20V MAX* XR® Brushless Cordless 1/4 Sheet Variable Speed Sander (Tool Only)



### DCW220B

20V MAX* XR® 3 in. x 21 in. Brushless Cordless Belt Sander (Tool Only)



Copyright ©2026 DEWALT. The following are trademarks for one or more DEWALT power tools, accessories, anchors and concrete adhesives: The yellow and black color scheme; the "D"-shaped air intake grill; the array of pyramids on the handgrip; the kit box configuration; and the array of lozenge-shaped humps on the surface of the tool.

1-800-4-DEWALT
WWW.DEWALT.COM